

Product Description

hence the name. Luminaire contains scale degrees for tilting and can be adjusted at maximum 25°.

Quick release magnetic front ring provides the option to change optional rings if required. Deep recessed LED position achieve minimal glare, and different beam angles can meet different lighting demand.

Choice of installation system is by clamp or spring, and quick and easy to install into all types of material and thicknesses thanks to fixing clamp mechanism


Product Specification

Luminaire Wattage	9W
Luminaire Color	<input type="checkbox"/> White <input checked="" type="checkbox"/> Black
Light Source	Lumileds 1202HD
Color Temperature	2700K/3000K/4000K
Color Rendering Index	Ra≥90
Beam Angle	15°/24°/36°
Luminous Flux	800lm at 3000K
cut-out	Ø75mm
Driver	LD9W250
Power Factor (PF)	≥0.50
Input	AC220-240V 50-60Hz
Output	DC 230-250mA 30-42V
Class	Class II
IP Degree	IP20
Inner Box	11X11X9.5cm
Carton Size	46X24X31cm
QTY/CTN	24PCS/CTN
Net Weight	0.2KG/PCS

Model No.

DSA0209S-C

CONTACT US FOR MORE DETAILS



Related references
Optional Accessories



DAB06-A

DAB06-B

DAB06-C

DAB06-D

Related references
LED POWER SUPPLIES



CE

Constant current power supply

Triac

0-10V

Dali

Brand: Eaglerise

Brand:

Cetificates:

Cetificates:

Related project picture of product family: